


15 AMP TRACK MOUNT CONTROL RELAYS


RIBM24C

4.00" Track Mount Relay 15 Amp **SPDT** with 24 Vac/dc Coil



RIBM24S

4.00" Track Mount Relay 15 Amp **SPST + Override** with 24 Vac/dc Coil



Made in USA
Meets
"Buy American"
of ARRA 2009



Cut
for
N/O

Cut
for
N/C

SPECIFICATIONS

Relays & Contact Type: One (1) SPDT Continuous Duty Coil (RIBM24C)
One (1) SPST Continuous Duty Coil (RIBM24S)

Expected Relay Life: 10 million cycles minimum mechanical

Operating Temperature: -30 to 140° F

Humidity Range: 5 to 95% (noncondensing)

Operate Time: 6ms

Relay Status: LED On = Activated

Dimensions: 1.250" x 4.000" x 1.750"

Track Mount: 4.000", See MT4 Series on page 152

MT4 Mounting Track Sold Separately

Approvals: UL Listed, UL916, UL864, C-UL
California State Fire Marshal

Gold Flash: No

Override Switch: No (RIBM24C)
Yes (RIBM24S)

Contact Ratings:

15 Amp General Use @ 125 Vac
10 Amp General Use @ 277 Vac
10 Amp Resistive @ 30 Vdc (N/O)
7 Amp Resistive @ 30 Vdc (N/C)
1/2 HP @ 125 Vac
1 HP @ 250 Vac
1/4 HP @ 277 Vac
C300 Pilot Duty

Coil Current:

26 mA @ 20 Vac
31 mA @ 24 Vac
48 mA @ 35 Vac
14 mA @ 20 Vdc
18 mA @ 24 Vdc
28 mA @ 35 Vdc

Coil Voltage Input:

24 Vac/dc ; 50-60 Hz
Drop Out = 3 Vac / 3.8 Vdc
Pull In = 20 Vac / 20 Vdc

Notes:

- Must cut appropriate jumper to select Normally Open or Normally Closed (RIBM24S)