

Programmable Thermostats

	Description	Model	Schedule Options		User Interface	Application		Dual Fuel	Power Method							Wiring Terminals		Accessories Included																								
			Temporary Override	Permanent Hold	Vacation Hold	Stages	Gas, Oil or Electric	Heat Pump	Millivolt	Lincvolt	Selectable Residential and Commercial	Balanced Point Lockout	Upstage Timer & Drop Settings		On Screen Help	Interview-Based Installer and User Programming	USB Port for Upgrading Geotemp and Geotemp Installer Setup	Micro SD for Upgrading Logo and Reset Installer Setup	Real-Time or Interval Sync (Automatically Updates Daylight Saving Time)	Time-of-Use Program Scheduling	Permanent Memory Retention	Selectable Auto or Manual Changeover	Auxiliary Heat Lockout	Adaptive Intelligent Recovery	Temperature Setpoint Limits	Keypad Lockout	Programmable & Circulation Fan Control	Humidification Control	Dehumidification Control	Ventilation Control	Tri-Lingual Language Options	Wireless Outdoor Sensor	Wired Outdoor Sensor	Wired Indoor Sensor	Wireless Indoor Sensor	Display Size (Viewable)	On-Demand Backlighting	Continuous Backlighting	Simultaneous Display of Room and Set Temperatures	Service Reminders	Limited Warranty	
Lyric®	Lyric Round™ Wi-Fi Thermostat	TH8732WFH5002 (US) TH8732WFH5010 (CAN)	Geofence, 7-day 5-1-1, 5-2-1 week, no schedule	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• •			C wire or phantom power	On app	Geofence help																			Filter only	5 Year	C, R, Rc, W-0/B, W2-AUX, Y, Y2, K, G, L, U1, U2	Trim ring, AAA lithium battery							
	Lyric™ T6 Pro Thermostat	TH6320WF2003	Geofence, 7-day 5-1-1, 5-2-1 week, no schedule	•	•	Through app	On device or Lyric app	Up to 3 Heat / 2 Cool - Heat Pump Up to 2 Heat / 2 Cool - Conventional	• •		C wire	On app	•					•			•												UWP mounting system, Honeywell standard installation adaptor (J-box adaptor), Honeywell decorative cover plate: small									
		TH6220WF2006	Geofence, 7-day 5-1-1, 5-2-1 week, no schedule	•	•	Through app	On device or Lyric app	Up to 2 Heat / 1 Cool - Heat Pump Up to 2 Heat / 2 Cool - Conventional	• •		C wire	On app	•					•			•											UWP mounting system, Honeywell standard installation adaptor (J-box adaptor), Honeywell decorative cover plate: small										
RedLINK and Wi-Fi Connected Thermostats	Prestige® IAQ Kits	YTHX9421R5127	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	• • •	•	2 wire only (R + C)	•	•	•			•		•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	•	•	5 Year	Prestige IAQ – R, C Equipment Interface Module – R, C, W-0/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, U3, RH, RC, R, C, S1, S2, S3, S4, S4	THM5421R1021 Equipment Interface Module, THM6000R1002 RedLINK™ Internet Gateway and 2 duct sensors							
		YTHX9421R5101	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	• • •	•	2 wire only (R + C)	•	•	•			•		•	•	•	•	•	•	•	•	•	8 sq. in.	•	•	•	•	5 Year	Prestige IAQ – R, C Equipment Interface Module – R, C, W-0/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, U3, RH, RC, R, C, S1, S2, S3, S4, S4	THM5421R1021 Equipment Interface module, C7089R1013 wireless outdoor sensor, and 2 duct sensors							
		YTHX9421R5085	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	• • •	•	2 wire only (R + C)	•	•	•			•		•	•	•	•	•	•	•	•	8 sq. in.	•	•	•	•	5 Year	Prestige IAQ – R, C Equipment Interface Module – R, C, W-0/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A, U1, U1, U2, U2, U3, U3, RH, RC, R, C, S1, S2, S3, S4, S4	THM5421R1021 Equipment Interface module, and 2 duct sensors								
	Prestige® Thermostat	THX9421R5021	7-Day or NP	•	•	•	Touchscreen	Up to 4 Heat/2 Cool – Heat Pump Up to 3 Heat/2 Cool – Conventional	• • •	•	2 wire only (R + C)	•	•	•			•		•	•	•	•	•	•	•	•	8 sq. in.	•	•	•	•	5 Year	Prestige IAQ – R, C Equipment Interface Module – R, C, W-0/B, W2/AUX1, W3/AUX2, Y, Y2, G, A-L/A – U1, U1, U2, U2, U3, U3, RH, RC, R, C, S1, S2, S3, S4, S4									
	Wi-Fi 9000	TH9320WF5003	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• •		C wire	•	•				•		•	•	•	•	•	•	•	•	8 sq. in.	•	•	•	•	5 Year	R, Rc, C, W-0/B, Y, G, W2-AUX/E, Y2, L, K	Filter, humidifier pad only								
Non-Connected Thermostats	EConnect™ Wireless Comfort System	YTL9160AR1000	7-Day or NP	•	•		Soft keys	1 Heat			Battery powered thermostat, 120/240V at EIM															4.53 sq. in.	•	•	•	•	3 Year	L1/L, L2/N & Load, Load	Antenna (with 2 covers white and beige) and EIM									
	RedLINK™ VisionPRO® 8000	TH8110R1008	7-Day or NP	•	•	•	Touchscreen	1 Heat/1 Cool***	• • •		Dual powered (battery and hardwire)	•	•				•	•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	•	•	5 Year	RC, C, W-0/B, Y, G, K, S1, S1									
		TH8320R1003	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional***	• • •	•	Dual powered (battery and hardwire)	•	•				•	•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	•	•	5 Year	R, RC, C, W-0/B, W2-AUX/E, Y, Y2, G, A-L/A, K, S1, S1									
		TH8321R1001	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional***	• • •	•	Dual powered (battery and hardwire)	•	•				•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	•	•	5 Year	R, RC, C, W-0/B, W2-AUX/E, Y, Y2, G, A-L/A, K, U1, U1, S1, S1										
		YTH8321R1002	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional***	• • •	•	Dual powered (battery and hardwire)	•	•				•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	•	•	5 Year	R, RC, C, W-0/B, W2-AUX/E, Y, Y2, G, A-L/A, K, U1, U1, S1, S1	RedLINK Internet Gateway									
	Wi-Fi VisionPRO® 8000	TH8321WF1001	7-Day or NP	•	•	•	Touchscreen	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• •		C wire	•	•				•	•	•	•	•	•	•	•	•	10 sq. in.	•	•	•	•	5 Year	A-L/A, R, RC, W2-AUX/E, Y, Y2, G, C, K, S1, S1, W-0/B, U1, U1										
Wireless FocusPRO® 6000 Programmable Kit*	Wireless FocusPRO® 6000 Programmable Kit*	YTH6320R1122	5-1-1/5-2	•	•		Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• •		Battery						•	•	•	•	•	•	•	•	•	5.09 sq. in.	•	•	•	•	5 Year	C, R, RC, RH, W-0/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS	RedLINK Internet Gateway, wireless outdoor sensor									
		YTH6320R1114	5-1-1/5-2	•	•		Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• •		Battery						•	•	•	•	•	•	•	•	•	5.09 sq. in.	•	•	•	•	5 Year	C, R, RC, RH, W-0/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS	RedLINK Internet Gateway and return air sensor									
		YTH6320R1001	5-1-1/5-2	•	•		Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• •		Battery						•	•	•	•	•	•	•	•	•	5.09 sq. in.	•	•	•	•	5 Year	C, R, RC, RH, W-0/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS	Return air sensor									
Non-Connected Thermostats	T6 PRO Thermostat	TH6320U2008	7-Day, 5-1-1, 5-2, or NP	•	•		Soft keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• • •		Dual powered (battery and hardwire)						•	•	•	•	•	•	•	•	•	5.44 sq. in.	•	•	•	•	5 Year	R, Rc, C, W, W2-AUX, Y, Y2, G, L, S, and S	UWP mounting system, Honeywell standard installation adaptor (J-box adaptor), Honeywell decorative cover plate: small									
		TH6220U2000	7-Day, 5-1-1, 5-2, or NP	•	•		Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• • •		Dual powered (battery and hardwire)						•	•	•	•	•	•	•	•	•	5.44 sq. in.	•	•	•	•	5 Year	R, Rc, C, W, W2-AUX, Y, Y2, G, L, S, and S	UWP mounting system, Honeywell standard installation adaptor (J-box adaptor), Honeywell decorative cover plate: small									
		TH6210U2001	7-Day, 5-1-1, 5-2, or NP	•	•		Soft keys	Up to 2 Heat/1 Cool – Heat Pump Up to 1 Heat/1 Cool – Conventional	• • •		Dual powered (battery and hardwire)						•	•	•	•	•	•	•	•	•	5.44 sq. in.	•	•	•	•	5 Year	R, Rc, C, W, W2-AUX, Y, G, L, and K	UWP mounting system, Honeywell standard installation adaptor (J-box adaptor), Honeywell decorative cover plate: small									
Non-Connected Thermostats	T4 Pro	TH4110U2005	7-day 5-1-1, 5-2, or NP	•	•		Soft keys	1 Heat/1 Cool	• • •		Dual powered (battery and hardwire)						•	•</																								

Non-Programmable Thermostats

Honeywell

	Description	Model	User Interface	Application	Stages	Gas, Oil or Electric	Heat Pump	Millivolt	Linevolt	Power Method	Permanent Memory Retention	Selectable Auto or Manual Changeover	Advanced Dual Fuel Heat Pump Operation	Comfort/Economy Mode	Temperature Setpoint Limits	Low Temperature Range	Remote Locator	Display Size (In/wable)	On-Demand Backlighting	Simultaneous Display of Room and Set Temperatures	Limited Warranty	Wiring Terminals	Accessories Included
	Wireless FocusPRO® 5000 Non-Programmable	YTH5320R1116	Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• •	Battery	•	•	•**	•	•	•***	5.09 sq. in.	•	•	5-Year	C, R, Rc, Rh, W-O/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS	RedLINK Internet Gateway, Wireless Outdoor Sensor and Return Air Sensor					
		YTH5320R1000	Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	• •	Battery	•	•	•**	•	•	•***	5.09 sq. in.	•	•	5-Year	C, R, Rc, Rh, W-O/B, W2-AUX/E, Y, Y2, G, L, RAS, RAS	Wireless Outdoor Sensor and Return Air Sensor					
	PRO 3000 Non-Programmable	TH3110D1008	Slide switches	1 Heat/1 Cool	• • •	Dual powered (battery and hardwire)	•	Manual					1.32 sq. in.	•	•	5-Year	R, Rc, C, W, O, B, Y, G						
		TH3210D1004	Slide switches	2Heat/1 Cool Heat Pump		Dual powered (battery and hardwire)	•	Manual					1.32 sq. in.	•	•	5-Year	R, C, Y, Aux, O, B, E, G, L						
	PRO 1000 Non-Programmable	TH1110DV1009 Vertical	Slide switches	1 Heat/1 Cool	• • •	Dual powered (battery and hardwire)	•	Manual					1.0 sq. in.	•		2-Year	R, Rc, C, W, Y, G, O, B						
		TH1110DH1003 Horizontal	Slide switches	1 Heat/1 Cool	• • •	Dual powered (battery and hardwire)	•	Manual					1.0 sq. in.	•		2-Year	R, Rc, C, W, Y, G, O, B						
		TH1100DV1000 Vertical	Slide switches	1 Heat	• • •	Dual powered (battery and hardwire)	•	Manual				•	1.0 sq. in.	•		2-Year	R, C, W						
		TH1100DH1004 Horizontal	Slide switches	1 Heat	• • •	Dual powered (battery and hardwire)	•	Manual				•	1.0 sq. in.	•		2-Year	R, C, W						
		TH1210DV1007 Vertical	Slide switches	2 Heat/1 Cool Heat Pump	•	Dual powered (battery and hardwire)	•	Manual					1.0 sq. in.	•		2-Year	R, C, AUX/E, O, B, Y, G						
		TH1210DH1001 Horizontal	Slide switches	2 Heat/1 Cool Heat Pump	•	Dual powered (battery and hardwire)	•	Manual					1.0 sq. in.	•		2-Year	R, C, AUX/E, O, B, Y, G						
	The Digital Round™	T8775A1009	Dial	1 Heat	•	Power stealing	•						.75 sq. in.	•		5-Year	R, W						
		T8775C1005	Dial	1 Heat/1 Cool	•	Power stealing	•	Manual					.75 sq. in.	•		5-Year	R, Rc, W, O, B, Y, G						
	The Round™	T87K1007	Dial	1 Heat or 1 Cool	•	Battery assisted power stealing					50010944-001		N/A	•		5-Year	R, W						
		T87N1000	Dial	1 Heat/1 Cool	•	Battery assisted power stealing		Manual			50010944-001		N/A	•		5-Year	R, Rc, W, Y, G, O, B						
		T87N1026	Easy-To-See™	1 Heat/1 Cool	•	Battery assisted power stealing		Manual			50010944-001		N/A	•		5-Year	R, Rc, W, Y, G, O, B						
		T834N1002 Vertical	Slide switches and lever	1 Heat/1 Cool	•	Mechanical		Manual			50019661-001		N/A			5-Year	R, Rc, W, Y, G, O, B						
		T8034N1007 Horizontal	Slide switches and lever	1 Heat/1 Cool	•	Mechanical		Manual			50019661-001		N/A			5-Year	R, Rc, W, Y, G, O, B						
		T822K1000	Slide switches and lever	1 Heat	•	Mechanical		Positive off			50019661-001		N/A			5-Year	R, W						
		T822K1018	Slide switches and lever	1 Heat	•	Mechanical					50019661-001		N/A			5-Year	R, W						
		T827K1009	Slide switches and lever	1 Heat	• •	Mechanical		Positive off			50019661-001		N/A			5-Year	R, W						
		TL7235A1003	Horizontal lags	1 Heat	•	208/240 V							2.67 sq. in.	•		5-Year	4 wire DPST						
		TL7230A1004	Dial	1 Heat	•	208/240 V							N/A			5-Year	DPST						
		T410/T4398	Dial	1 Heat	•	120/208/240/277 V							N/A			1-Year	SPST or DPST						