




<http://www.functionaldevices.com>

AT SERIES		4.00" wide AdapTrack® for relays, current sensors, and power supplies																										
  <p>Model Shown: AT4-6</p> <p>Functional Devices, Inc. A600A 2003</p>																												
<p>GENERAL SPECIFICATIONS</p> <p>Approvals: UL Component Recognized; USA & Canada Flame Rated: 94-5V DIN Rail Sizes: 32 mm x 1.5mm asymmetrical DIN rail EN50035 35mm x 7.5mm symmetrical DIN rail EN50022 22.4mm x 6.9mm symmetrical NEMA A Series rail</p>		<p style="text-align: center;">AT SERIES ADAPTRACK® SELECTION GUIDE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="background-color: black; color: white;">Model #</th> <th style="background-color: black; color: white;">Width</th> <th style="background-color: black; color: white;">Length</th> <th style="background-color: black; color: white;">DIN Rail Sizes</th> </tr> </thead> <tbody> <tr> <td>AT4-2</td> <td style="text-align: center;">4.00"</td> <td style="text-align: center;">2.00"</td> <td>3 Most Common (See General Specifications to the left)</td> </tr> <tr> <td>AT4-6</td> <td style="text-align: center;">4.00"</td> <td style="text-align: center;">3.00"</td> <td>3 Most Common (See General Specifications to the left)</td> </tr> <tr> <td>AT4-12</td> <td style="text-align: center;">4.00"</td> <td style="text-align: center;">12.00"</td> <td>3 Most Common (See General Specifications to the left)</td> </tr> <tr> <td>AT4-24</td> <td style="text-align: center;">4.00"</td> <td style="text-align: center;">24.00"</td> <td>3 Most Common (See General Specifications to the left)</td> </tr> <tr> <td>AT4-48</td> <td style="text-align: center;">4.00"</td> <td style="text-align: center;">48.00"</td> <td>3 Most Common (See General Specifications to the left)</td> </tr> </tbody> </table>			Model #	Width	Length	DIN Rail Sizes	AT4-2	4.00"	2.00"	3 Most Common (See General Specifications to the left)	AT4-6	4.00"	3.00"	3 Most Common (See General Specifications to the left)	AT4-12	4.00"	12.00"	3 Most Common (See General Specifications to the left)	AT4-24	4.00"	24.00"	3 Most Common (See General Specifications to the left)	AT4-48	4.00"	48.00"	3 Most Common (See General Specifications to the left)
Model #	Width	Length	DIN Rail Sizes																									
AT4-2	4.00"	2.00"	3 Most Common (See General Specifications to the left)																									
AT4-6	4.00"	3.00"	3 Most Common (See General Specifications to the left)																									
AT4-12	4.00"	12.00"	3 Most Common (See General Specifications to the left)																									
AT4-24	4.00"	24.00"	3 Most Common (See General Specifications to the left)																									
AT4-48	4.00"	48.00"	3 Most Common (See General Specifications to the left)																									
<p style="text-align: center;">NOTES</p> <p>AT4 AdapTrack® snaps onto the three most common DIN Rail Sizes to provide mounting for 4" wide panel style relays, current sensors, and power supplies.</p>																												

NOTES: