


**15 AMP TRACK MOUNT CONTROL RELAYS**


**RIBM24C**

4.00" Track Mount Relay 15 Amp SPDT with 24 Vac/dc Coil



**RIBM24S**

4.00" Track Mount Relay 15 Amp SPST + Override with 24 Vac/dc Coil



RELAYS

**SPECIFICATIONS**

- # Relays & Contact Type:** One (1) SPDT Continuous Duty Coil (RIBM24C)  
One (1) SPST Continuous Duty Coil (RIBM24S)
- Expected Relay Life:** 10 million cycles minimum mechanical
- Operating Temperature:** -30 to 140° F
- Humidity Range:** 5 to 95% (noncondensing)
- Operate Time:** 6ms
- Relay Status:** LED On = Activated
- Dimensions:** 1.250" x 4.000" x 1.750"
- Track Mount:** 4.000", See MT4 Series on page 152  
**MT4 Mounting Track Sold Separately**
- Approvals:** UL Listed, UL916, UL864, C-UL  
California State Fire Marshal
- Gold Flash:** No
- Override Switch:** No (RIBM24C)  
Yes (RIBM24S)

- Contact Ratings:**  
15 Amp General Use @ 125 Vac  
10 Amp General Use @ 277 Vac  
10 Amp Resistive @ 30 Vdc (N/O)  
7 Amp Resistive @ 30 Vdc (N/C)  
1/2 HP @ 125 Vac  
1 HP @ 250 Vac  
1/4 HP @ 277 Vac  
C300 Pilot Duty

- Coil Current:**  
26 mA @ 20 Vac  
31 mA @ 24 Vac  
48 mA @ 35 Vac  
14 mA @ 20 Vdc  
18 mA @ 24 Vdc  
28 mA @ 35 Vdc

- Coil Voltage Input:**  
24 Vac/dc ; 50-60 Hz  
Drop Out = 3 Vac / 3.8 Vdc  
Pull In = 20 Vac / 20 Vdc

- Notes:**  
• Must cut appropriate jumper to select Normally Open or Normally Closed (RIBM24S)